



# DATA SHEET

## CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**  
**1 CF 71 NP**
- ▶ **Nitta Japan code:**



**CONSTRUCTION:** 1 ply cotton/polyester, non-rigid

<b>TOP COVER:</b>	<b>Material:</b>	PVC	
	<b>Top thickness:</b>	0,7	mm (approx.)
	<b>Colour:</b>	white	
	<b>Hardness:</b>	55A	
	<b>Profile:</b>	NP	

**BOTTOM SIDE:** Fabric

<b>Total thickness:</b>	2,2	mm (approx.)
<b>Weight:</b>	2,1	kg/m <sup>2</sup> (approx.)
<b>Max. width:</b>	2000	mm
<b>Belt support:</b>	not applicable	

<b>Rating at 1% elongation:</b>	n.a.	N/mm
<b>Advised pretension:</b>	n.a.	N/mm
<b>Maximum allowable tension:</b>	n.a.	N/mm
<b>Temperature range:</b>	-10 to +110	°C

<b>Minimum pulley diameters:</b>		
<b>Flexing:</b>	n.a.	mm
<b>Backflexing:</b>	n.a.	mm

**Special approval:** FDA, 10/2011/EC + amendments

**Applications:** As drum - lagging material  
Oil and grease resistant

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: [www.nitta.nl](http://www.nitta.nl)



**NITTA CORPORATION  
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail [sales@nitta.nl](mailto:sales@nitta.nl) - [www.nitta.nl](http://www.nitta.nl)

Date of issue: 08-09-2011