



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
1 RF 709 V
- ▶ **Nitta Japan code:**



CONSTRUCTION: 1 ply polyester, rigid

TOP COVER:

Material:	Felt	
Top thickness:	1,8	mm (approx.)
Colour:	white	
Hardness:	-	
Profile:		

BOTTOM SIDE: Fabric

Total thickness:	3,1	mm (approx.)
Weight:	2,4	kg/m ² (approx.)
Max. width:	2000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	5	N/mm
Advised pretension:	2-4	N/mm
Maximum allowable tension:	8	N/mm
Temperature range:	-10 to 90	°C

Minimum pulley diameters:

Flexing:	30	mm
Backflexing:	45	mm

Special approval: FDA, 10/2011/EC + amendments

Applications: Conveyor belt in bakeries
Proofer cabinets
Excellent release of dough in bakeries
Oil and grease resistant

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 08-09-2011