



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
2 CF
- ▶ **Nitta Japan code:**
CC-12DKC



CONSTRUCTION: 2 plies cotton/polyester, non-rigid

TOP COVER:

Material:	Fabric
Top thickness:	- mm (approx.)
Colour:	
Hardness:	-
Profile:	

BOTTOM SIDE: Cotton/polyester fabric

Total thickness:	1,8	mm (approx.)
Weight:	1,9	kg/m ² (approx.)
Max. width:	2000	mm
Belt support:	sliderbed, (rollers) flat + troughed	

Rating at 1% elongation:	8	N/mm
Advised pretension:	4-7	N/mm
Maximum allowable tension:	10	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:

Flexing:	20	mm
Backflexing:	20	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Conveyor belt in bakeries
- Excellent release of dough in bakeries
- Conveying of (un)vulcanised rubber
- In laundries
- In the leather and hide industry

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 08-09-2011