



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
2 LRAFP 02/W2 IM M 1,4
- ▶ **Nitta Japan code:**



CONSTRUCTION: 2 plies polyester, rigid, antistatic

TOP COVER:	Material:	PU	
	Top thickness:	0,2	mm (approx.)
	Colour:	white	
	Hardness:	87A	
	Profile:	matt	

BOTTOM SIDE: Impregnated fabric

Total thickness:	1,4	mm (approx.)
Weight:	1,5	kg/m ² (approx.)
Max. width:	2000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	8	N/mm
Advised pretension:	4-7	N/mm
Maximum allowable tension:	12	N/mm
Temperature range:	-20 to +80	°C

Minimum pulley diameters:		
Flexing:	8 to 10	mm
Backflexing:	20	mm

Special approval: FDA, 10/2011/EC + amendments

Applications: Conveyor belt for the food industry
Accumulation belt
Conveyor belt in bakeries
Cooling belt in bakeries
Oil and grease resistant

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 08-09-2011