



# DATA SHEET

## CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**  
**2 LRAFP IM 0,9**
- ▶ **Nitta Japan code:**



**CONSTRUCTION:** 2 plies polyester, rigid, antistatic

**TOP COVER:**

<b>Material:</b>	PU	
<b>Top thickness:</b>	-	mm (approx.)
<b>Colour:</b>	clear	
<b>Hardness:</b>	-	
<b>Profile:</b>		

**BOTTOM SIDE:** Impregnated fabric

<b>Total thickness:</b>	0,9	mm (approx.)
<b>Weight:</b>	1	kg/m <sup>2</sup> (approx.)
<b>Max. width:</b>	2000	mm
<b>Belt support:</b>	sliderbed, (rollers) flat	

<b>Rating at 1% elongation:</b>	5	N/mm
<b>Advised pretension:</b>	2-3	N/mm
<b>Maximum allowable tension:</b>	9	N/mm
<b>Temperature range:</b>	-20 to +80	°C

**Minimum pulley diameters:**

<b>Flexing:</b>	12	mm
<b>Backflexing:</b>	20	mm

**Special approval:** FDA, 10/2011/EC + amendments

**Applications:** Dough handling in bakeries  
Proofer cabinets  
Retractory conveyors  
Oil and grease resistant

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: [www.nitta.nl](http://www.nitta.nl)



**NITTA CORPORATION  
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail [sales@nitta.nl](mailto:sales@nitta.nl) - [www.nitta.nl](http://www.nitta.nl)

Date of issue: 08-09-2011