



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
2 LRF 704/001
- ▶ **Nitta Japan code:**
CC-12AK



CONSTRUCTION: 2 plies polyester, rigid

TOP COVER:

Material:	PVC	
Top thickness:	0,4	mm (approx.)
Colour:	white	
Hardness:	65A	
Profile:		

BOTTOM SIDE: Impregnated fabric

Total thickness:	2,1	mm (approx.)
Weight:	2,5	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	8	N/mm
Advised pretension:	4-7	N/mm
Maximum allowable tension:	12	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:

Flexing:	25	mm
Backflexing:	50	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Conveyor belt for the food industry
- Conveying of meat, fish and poultry products
- In the dairy and bakery industry
- Cooling belt in bakeries
- Oil and grease resistant

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 08-09-2011