



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
2 LRF 2704
- ▶ **Nitta Japan code:**



CONSTRUCTION: 2 plies polyester, rigid

TOP COVER:

Material:	PVC	
Top thickness:	0,4	mm (approx.)
Colour:	Nitta colour	
Hardness:	80A	
Profile:		

BOTTOM SIDE: Fabric

Total thickness:	2,0	mm (approx.)
Weight:	2,3	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	8	N/mm
Advised pretension:	4-7	N/mm
Maximum allowable tension:	12	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:

Flexing:	25	mm
Backflexing:	50	mm

Special approval: -

Applications: General purpose conveying
Conveying fruit and vegetables
Conveying of boxes in packaging lines
Conveying of tobacco and tea

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 30-11-2010