



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
1 RWAF 907 NDP AS
- ▶ **Nitta Japan code:**



CONSTRUCTION: 1 ply polyester, rigid, antistatic

TOP COVER:

Material:	PVC	
Top thickness:	0,7	mm (approx.)
Colour:	black	
Hardness:	85A	
Profile:	NDP	

BOTTOM SIDE: Whisper fabric

Total thickness:	1,8	mm (approx.)
Weight:	1,4	kg/m ² (approx.)
Max. width:	2000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	5	N/mm
Advised pretension:	2-4	N/mm
Maximum allowable tension:	9	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:

Flexing:	20	mm
Backflexing:	50	mm

Special approval: -

Applications: Jogging machines (treadmills)
Light duty conveyor belt

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 27-12-2010