



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
2 LRWAF 907 SQPR
- ▶ **Nitta Japan code:**



CONSTRUCTION: 2 plies polyester, rigid, antistatic

TOP COVER:	Material:	PVC	
	Top thickness:	0,7	mm (approx.)
	Colour:	black	
	Hardness:	80A	
	Profile:	SQPR	

BOTTOM SIDE: Whisper fabric

Total thickness:	2,7	mm (approx.)
Weight:	2,7	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	9	N/mm
Advised pretension:	4-7	N/mm
Maximum allowable tension:	16	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	50	mm
Backflexing:	75	mm

Special approval: -

Applications: Jogging machines (treadmills)
General purpose conveying

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 27-12-2010